



**CROSS LINKED POLYETHYLENE PIPE**  
*OXYGEN BARRIER (RED)*

**OXYPEX** is oxygen barrier tubing manufactured to NSF 14, ASTM F876/F877 and CSA Standard B137.5 designed for use in closed loop Hydronic Heating Applications.

**OXYPEX** meets DIN Standard 4726 as endorsed by the Hydronics Institute. Coil lengths up to 1000 feet are foot marked for installation convenience.

**OXYPEX** comes in a distinctive "Red" color.



CSA B137.5  
 NSF 61 & 14  
 DIN 4726



COIL LENGTHS UP TO 1000 FEET  
 WITH FOOT MARKS FOR INSTALLATION CONVENIENCE  
 ALL SIZING IS NOMINAL COPPER TUBE SIZE (CTS)

100 PSI @ 82°C (180°F)  
 160 PSI @ 23°C ( 73°F)  
 80 PSI @ 93°C (200°F)

LENGTHS					
ITEM	DIMENSION NOMINAL	DIMENSION O.D.	LENGTHS	QTY/PKG	PRICE PER 100'
588764	1/2"	.625	20'	500'	132.06
588772	3/4"	.875	20'	200'	188.02
587378	1"	1.125	20'	100'	406.24
COILS					
ITEM	DIMENSION NOMINAL	DIMENSION O.D.	COILS	QTY/PKG	PRICE PER 100'
587923	3/8"	.500	100'	100'	104.89
587246	3/8"	.500	300'	300'	104.89
587253	3/8"	.500	500'	500'	104.89
587261	3/8"	.500	1000'	1000'	104.89
589978	1/2"	.625	100'	100'	132.06
588137	1/2"	.625	250'	250'	132.06
587410	1/2"	.625	300'	300'	132.06
588475	1/2"	.625	500'	500'	132.06
588145	1/2"	.625	1000'	1000'	132.06
587816	1/2"	.625	1200'	1200'	132.06
587931	5/8"	.750	100'	100'	152.96
587279	5/8"	.750	300'	300'	152.96
587287	5/8"	.750	400'	400'	152.96
587295	5/8"	.750	500'	500'	152.96
587303	5/8"	.750	1000'	1000'	152.96
587964	3/4"	.875	100'	100'	188.02
588178	3/4"	.875	250'	250'	188.02
587949	3/4"	.875	300'	300'	188.02
588483	3/4"	.875	500'	500'	188.02
588251	3/4"	.875	1000'	1000'	188.02
587477	1"	1.125	100'	100'	406.24
587188	1"	1.125	300'	300'	406.24
587386	1"	1.125	500'	500'	406.24