

\$30 INSTANT REBATE

Prices valid through December 31, 2018.



007E™ ECM HIGH-EFFICIENCY CIRCULATOR

- Ideal for hydronic systems zoned with circulators or zone valves
- 10 ft. shut-off head, 16 gpm max flow
- BIO BARRIER® protects pump from contaminants
- SureStart automatically frees locked rotor condition and self-purges air from pump
- Integral Flow Check (IFC®) included
- Cast iron, standard flange, 2-bolt

| Item ID | Flange | Mfg No. |
|---------|-----------|---------|
| DA9924 | Standard | 007e-F2 |
| DA9922 | Universal | 007e-F4 |



0015E3 ECM HIGH-EFFICIENCY CIRCULATOR

- 3 easy settings: LOW (5 feet head), MEDIUM (10 feet head), HIGH (18 feet head), 16 gpm max flow
- Dual electrical knockouts, 6" stranded wire leads included
- Use with a Taco ZVC Zone Valve Control or SR Switching Relay for ON/OFF operation
- Optional 2-way flange model provides universal fit-up to any flange position
- Double insulated — no ground wire required
- Whisper quiet operation

| Item ID | Flange | Mfg No. |
|---------|-----------|-----------|
| DA9923 | Standard | 0015e3-F2 |
| DA9921 | Universal | 0015e3-F4 |



00E™ ECM HIGH-EFFICIENCY CIRCULATOR

- High-efficiency ECM motor uses up to 85% less electricity
- 18 ft. shut-off head, 16 gpm max flow
- Infinitely variable speed settings for fine tuning flow
- SureStart automatic unblocking and air purging mode
- Dual electrical knock-outs and 6" stranded wire leads included for easy wiring
- Easy to use dial to set operating speed or pressure control
- BIO BARRIER® filter protects pump from contaminants

| Item ID | Flange | Mfg No. |
|----------|-----------|-------------------|
| DA9925 | Standard | VR1816-HY1-FC2A00 |
| DA992525 | Universal | VR1816-HY1-4C2A00 |



Three convenient ways to order: 800.444.0101 • Fax 800.444.7718 • designair.com